



**Artikel Nr.: 341020**

Wandaufbauleuchte, Specular II, Silber, 220-240V AC/50-60Hz, 150,00 W

**Technische Daten**

**Charakteristik**

<b>Material</b>	Glas
<b>Farbe</b>	Silber
<b>Optik</b>	verspiegelt
<b>im Lieferumfang</b>	



**Elektrische Daten**

<b>Leistung</b>	150,00 W
<b>Eingangsspannung</b>	220-240V AC/50-60Hz
<b>Eingangsstrom</b>	
<b>Fassung / Sockel</b>	R7S 78mm
<b>Anzahl Sockel</b>	1
<b>Netzgerät</b>	
<b>Ansteuerung</b>	Phasenanschnitt oder Phasenabschnitt
<b>Anschlussmöglichkeit</b>	Klemme
<b>Schutzklasse I, II, III</b>	I





## Artikel Nr.: 341020

Wandaufbauleuchte, Specular II, Silber, 220-240V AC/50-60Hz, 150,00 W

### Lichtrichtung

Dreh- und Schwenkbereich	schwenkbar
Neigungswinkel	
Abstrahlverhalten	
Reflektor / Linse	

### Abmessungen und Gewicht

Länge	200 mm
Breite	140 mm
Höhe	160 mm
Durchmesser	
Deckenabhängung	
Gewicht	908 g

### Rosettenmaß

Länge	200 mm
Breite	42 mm
Höhe	
Durchmesser	



**Artikel Nr.: 341020**

Wandaufbauleuchte, Specular II, Silber, 220-240V AC/50-60Hz, 150,00 W

**Grenzwerte**

Betriebstemperatur	-5°C - +40°C
Lagertemperatur	
IP - Schutzart	IP 20

**IP 20**

Schutz gegen das Eindringen von Fremdkörper > 50 mm. Kein Schutz gegen das Eindringen von Wasser.



Leuchte der Schutzklasse I bei der der Schutz gegen elektrischen Schlag nicht allein auf der Basisisolierung beruht, sondern die eine zusätzliche Sicherheitsvorkehrung derart enthält, dass berührbare leitfähige Teile mit Mitteln zum Anschluss an den Schutzleiter der festen Installation ausgerüstet sind, so dass im Fehlerfall der Basisisolierung berührbare leitfähige Teile nicht aktiv werden können.



**Article no.: 341020**

Surface mounted wall lamp, Specular II, silver, 220-240V AC/50-60Hz, 150,00 W



**Technical Data**

**General Characteristics**

<b>Material</b>	glass
<b>Colour</b>	silver
<b>Optics</b>	mirror
<b>included in delivery</b>	

**Electrical Characteristics**

<b>Wattage</b>	150,00 W
<b>Input voltage</b>	220-240V AC/50-60Hz
<b>Input current</b>	
<b>Base (standard designation)</b>	R7S 78mm
<b>Number of bases</b>	1
<b>Power supply unit</b>	
<b>Electronically reversible</b>	Phase Angle or Phase Section
<b>Connection possibility</b>	clamp
<b>Protection class I, II, III</b>	I





## Article no.: 341020

Surface mounted wall lamp, Specular II, silver, 220-240V AC/50-60Hz, 150,00 W

### Light Direction

Rotating and tilting range	swivel
Angle of inclination	
Radiation direction	
Reflector / lense	

### Dimensions & Weight

Length	200 mm
Width	140 mm
Height	160 mm
Diameter	
Suspensions from ceiling	
Product Weight	908 g

### Rosette dimensions

Length	200 mm
Width	42 mm
Height	
Diameter	



## Article no.: 341020

Surface mounted wall lamp, Specular II, silver, 220-240V AC/50-60Hz, 150,00 W

### Absolute maximum ratings

Working temperature	-5°C - +40°C
Storage temperature	
IP - Code	IP 20

#### IP 20

Protection against penetration of foreign objects > 50 mm. No protection against penetration of water.



Lightings of Protection Class I in which the protection against electric shock is not based solely on isolation, but an additional safety measure contains such a way that accessible conductive parts are equipped with means for connection to the protective conductor of the fixed installation, so that in case of failure of the basic insulation exposed conductive parts cannot be active.